



Front ITO film 0.188mm  
 hard coating anti newton ring  
 Back ITO glass 1.1mm

Thick: 1.4 ± 0.15

- Instruction:
- Type: Film to Glass
  - Operating Voltage: ≤10V
  - Response Time: ≤10ms
  - Storage Temperature: -20℃~+70℃
  - Operation Temperature/Humidity: -10℃~+60℃/ 20%~95%
  - Hitting Life: >10,000,000 Times, 250gf Force;
  - writing Life: >1,000,000 Times 250gf Force;
  - Connect Material: FPC+PIN
  - Film Thickness: 0.188mm
  - Glass Thickness: 1.1mm
  - Light transmission: ≥78%
  - Force: 100g or more
  - Linearity: ≤5%
  - Insulation: ≥20MΩ
  - Resistance: 50Ω < PIN1, PIN2 < 250Ω  
50Ω < PIN2, PIN4 < 250Ω  
50Ω < PIN4, PIN5 < 250Ω  
50Ω < PIN6, PIN1 < 250Ω
  - Surface Hardness ≥3H (pencil)

# TouchKit-0800-W5R

## REVISIONS

| SCALE   | 1:1         | MATERIAL  | F/G      | Version |
|---------|-------------|-----------|----------|---------|
| UNIT    | MM          | TOLERANCE | ±0.3mm   | NO.     |
| DESIGN  | Layer       | DATE      | 20090709 | 1 of 1  |
| CHECK   | Pecker * LI | DATE      | 20090709 |         |
| RELEASE | Value       | DATE      | 20090709 |         |

# TouchKit