



Instruction:  
 1.Type: Film to Glass  
 2. Operating Voltage: ≤10V  
 3. Response Time: ≤10ms  
 4. Storage Temperature: -20℃~+70℃  
 5. Operation Temperature/Humidity: -10℃~+60℃/ 20%~95%  
 6. Hitting Life: >10,000,000 Times, 250gf Force;  
 7. Writing Life: >1,000,000 Times 250gf Force;  
 8. Connect Material: FPC+PIN

9. Film Thickness: 0.188mm  
 10. Glass Thickness: 1.8mm  
 11. Light transmission: ≥73%  
 12. Force: 100g or more  
 13. Linearity: ≤5%  
 14. Insulation: ≥20MΩ  
 15. Resistance: 50Ω < PIN1, PIN2 < 250Ω  
 50Ω < PIN3, PIN4 < 250Ω  
 50Ω < PIN5, PIN6 < 250Ω  
 16. Surface Hardness: ≥3H (pencil)

Front: ITO Film—0.188mm  
 Anti newton ring  
 Back Glass—1.8mm

TouchKit-1710-W5R-A

REVISIONS

SCALE	1:1	MATERIAL	F/G	Version	1.0
UNIT	MM	TOLERANCE	±0.3m	No. - 1 of 1	
DESIGN	Lucy	DATE	20090505		
CHECK	Peter * LI	DATE	20090505		
RELEASE	Victor	DATE	20090505		

**TOUCHKIT**